

## DAFTAR PUSTAKA

- [1] N. I. Fauziyah, *Perancangan Sistem Kendali Robot Tangan Berbasis Jaringan Syaraf Tiruan Dan Synergy Feature*. 2019.
- [2] M. Rahman, *Rancang Bangun Prostesis Lengan Untuk Tunadaksa Bawah Siku (Amputasi Transradial)*. 2017.
- [3] A. P. Schulz, S. Fuchs, L. Simon, K. Seide, A. Paech, and C. Queitsch, “Severe fracture of the Tibial Pilon: Results with a multidirectional self-locking osteosynthesis plate utilizing a two-stage procedure,” *Eur. J. Trauma Emerg. Surg.*, vol. 34, no. 4, pp. 391–396, 2008, doi: 10.1007/s00068-007-2209-6.
- [4] N. Rachmat, “Pengaruh Penggunaan Kaki Palsu terhadap Kepercayaan Diri Pasien Post Amputasi Kaki,” *J. Kesehatan.*, vol. 7, no. 1, p. 101, 2016, doi: 10.26630/jk.v7i1.126.
- [5] E. P. S. Oeoen, Jondri, and U. N. Wisesty, “Klasifikasi Pergerakan Jari Tangan Berdasarkan Sinyal EMG Menggunakan Stacked Denoising

Autoencoder untuk Mengendalikan Tangan Prostetik,” *e-Proceeding Eng.*, vol. 5, no. 3, pp. 7782–7789, 2018.

- [6] R. E. Russo, J. G. Fernández, and R. R. Rivera, “Algorithm of Myoelectric Signals Processing for the Control of Prosthetic Robotic Hands,” *J. Comput. Sci. Technol.*, vol. 18, no. 01, p. e04, 2018, doi: 10.24215/16666038.18.e04.
- [7] M. N. Robby, “Perancangan Simulator Gerak dan Sistem Monitoring untuk Menggerakkan dan Memonitoring Tangan Palsu Elektrik,” p. 82, 2017.
- [8] Y. Su, M. H. Fisher, A. Wolczowski, G. D. Bell, D. Burn, and R. Gao, “Towards an EMG Controlled Prosthetic Hand Using a 3D Electromagnetic Positioning System,” *2005 IEEE Instrumentation and Meas. Technol. Conf. Proc.*, vol. 1, no. October 2016, pp. 261–266, 2005, doi: 10.1109/IMTC.2005.1604113.
- [9] L. S. Praveen, S. N. Nagananda, and P. Shankapal, “Design and Development of Real Time Bionic Hand Control Using EMG Signal,” *2018 IEEE Int. Conf. Electron. Comput. Commun. Technol.*

- CONECCT 2018*, pp. 1–4, 2018, doi: 10.1109/CONECCT.2018.8482393.
- [10] M. Snajdarova, J. Barabas, R. Radil, and O. Hock, “Proof of concept EMG-Controlled prosthetic hand system - An overview,” *Proc. 2018 19th Int. Conf. Comput. Probl. Electr. Eng. CPEE 2018*, pp. 1–4, 2018, doi: 10.1109/CPEE.2018.8506896.
- [11] D. Damodar, “Myoelectric Hand : Prosthetic hand replication using EMG based approach,” no. September, pp. 3–8, 2018, doi: 10.13140/RG.2.2.11237.04323.
- [12] G. S. Rash, “Electromyography: Fundamentals,” *Int. Encycl. Ergon. Hum. Factors - 3 Vol. Set*, pp. 3155–3162, 2021, doi: 10.1201/9780849375477-621.
- [13] T. Sono, L. Menegaldo, and M. Pinotti, “Hand prosthesis prototype controlled by EMG and vibrotactile force feedback,” *Proc. IEEE RAS EMBS Int. Conf. Biomed. Robot. Biomechatronics*, pp. 91–95, 2014, doi: 10.1109/biorob.2014.6913758.
- [14] O. Lagerquist, Æ. E. P. Zehr, Æ. E. R. L. Baldwin,

P. M. Klakowicz, and Æ. D. F. Collins, “Diurnal changes in the amplitude of the Hoffmann reflex in the human soleus but not in the flexor carpi radialis muscle,” pp. 1–6, 2006, doi: 10.1007/s00221-005-0172-1.

[15] O. Lagerquist, Æ. E. P. Zehr, Æ. E. Rl, P. M. Klakowicz, and Æ. D. F. Collins, “Perubahan diurnal dalam amplitudo refleks Hoffmann pada soleus manusia tetapi tidak pada otot fleksor karpi radialis,” pp. 1–6, 2006, doi: 10.1007/s00221-005-0172-1.

[16] M. Yoshikawa, R. Sato, T. Higashihara, T. Ogasawara, and N. Kawashima, “Rehand : Realistic Electric Prosthetic Hand Created with a 3D Printer,” pp. 2470–2473, 2015.

[17] K. J. Krieger, J. Liegey, E. M. Cahill, N. Bertollo, M. M. Lowery, and E. D. O’Cearbhaill, “Development and Evaluation of 3D-Printed Dry Microneedle Electrodes for Surface Electromyography,” *Adv. Mater. Technol.*, vol. 5, no. 10, pp. 1–13, 2020, doi: 10.1002/admt.202000518.

- [18] U. Raza and H. Syed Tahir Rizvi, "Implementation of Prosthetic Hand through EMG Signals," *5th World Eng. Congr.*, 2013.
- [19] A. Reust and J. Desai, "Development of an EMG Controlled Robotic Hand Prosthesis Development of an EMG Controlled Robotic Hand Prosthesis," no. April, pp. 6–8, 2017.
- [20] A. Cranny, D. P. J. Cotton, P. H. Chappell, S. P. Beeby, and N. M. White, "Thick-film force, slip and temperature sensors for a prosthetic hand," *Meas. Sci. Technol.*, vol. 16, no. 4, pp. 931–941, 2005, doi: 10.1088/0957-0233/16/4/005.
- [21] P. Konrad, "ABCofEMG.pdf," no. April, pp. 1–60, 2005.
- [22] A. I. F. Dwi, "Klasifikasi Sinyal Emg Dari Otot Lengan Sebagai Media Kontrol Menggunakan Naïve Bayes," *Inst. Teknol. Sepuluh Nop.*, p. 16, 2017.
- [23] C. J. De Luca, "Surface electromyography: Detection and recording," *DelSys Inc.*, vol. 10, no. 2, pp. 1–10, 2002, [Online]. Available: <http://scholar.google.com/scholar?hl=en&btnG=S>

earch&q=intitle:SURFACE+ELECTROMYOGR  
APHY+:+DETECTION+AND+RECORDING#0.

- [24] DFRobot, “No Title,” [Online]. Available: <https://www.dfrobot.com/product-1661.html>.
- [25] DFRobot, “Analog EMG Sensor by OYMotion SKU: SEN0240,” 2017, [Online]. Available: [https://media.digikey.com/pdf/Data Sheets/DFRobot PDFs/SEN0240\\_Web.pdf](https://media.digikey.com/pdf/Data Sheets/DFRobot PDFs/SEN0240_Web.pdf).
- [26] ESP, “No Title.” <https://timur.ilearning.me/2019/04/19/mikrokontroler-esp32-apa-itu/>.
- [27] ESP, “ESP32 Series Datasheet,” *Espr. Syst.*, pp. 1–65, 2021, [Online]. Available: [https://www.espressif.com/sites/default/files/documentation/esp32\\_datasheet\\_en.pdf](https://www.espressif.com/sites/default/files/documentation/esp32_datasheet_en.pdf).
- [28] A. Rianto and R. Kristiyono, “Aplikasi Sensor HCSR04 Untuk Mengukur Jarak Ketinggian Air Dengan Mikrokontrol Wemos D1 R2 Berbasis IoT (Internet of Things),” *J. Tek.*, vol. 6, pp. 141–148, 2020.