

## DAFTAR PUSTAKA

- [1] S. Purwiyanti, S. R. Sulistiyanti, F. A. Setyawan, B. M. Wibisono, K. S. Atmaja, and H. Fitriawan, “Multisensors System for Real Time Detection of Length, Weight, and Heartbeat of Premature Baby in the Incubator,” *Proc. 2018 Int. Conf. Electr. Eng. Comput. Sci. ICECOS 2018*, vol. 17, pp. 85–88, 2019, doi: 10.1109/ICECOS.2018.8605208.
- [2] W. A. AKBAR and H. H. RACHMAT, “Rancang Bangun Sistem Pengukur Massa Tubuh dan Panjang Badan Elektronik Terintegrasi untuk Evaluasi Gizi Balita,” *ELKOMIKA J. Tek. Energi Elektr. Tek. Telekomun. Tek. Elektron.*, vol. 6, no. 1, p. 125, 2018, doi: 10.26760/elkomika.v6i1.125.
- [3] B. Wahyudi, D. J. Adella, and M. U. Nuha ABA, “Analisis Data Berat Badan Dan Panjang Bayi Dengan Alat Ukur Panjang Dan Berat Badan Bayi Berbasis Arduino,” *Elektrika*, vol. 13, no. 2, p. 42, 2021, doi: 10.26623/elektrika.v13i2.3161.
- [4] M. S. Bambang GI, Dwi Herry, *Rancang Bangun Sentral Baby Inkubator Berbasis Telemedicine*, no.

Oktober. 2021.

- [5] S. Y. Setiawan, D. H. Andayani, A. Pudji, L. Soetjatie, and A. B. Anugrah Kusuma, “Analysis Of Baby Incubator Humidity Based PID with Kangaroo Mode,” *J. Electron. Electromed. Eng. Med. Informatics*, vol. 4, no. 1, pp. 50–54, 2022, doi: 10.35882/jeeemi.v4i1.6.
- [6] S. Hamrioui, C. A. M. Hamrioui, and P. Lorenz, “Distinction between data losses for better communications in IoT,” *2017 Int. Conf. Adv. Comput. Commun. Informatics, ICACCI 2017*, vol. 2017-Janua, pp. 494–500, 2017, doi: 10.1109/ICACCI.2017.8125888.
- [7] W. J. Telaumbanua, “Hybrid Network untuk Pengembangan Internet of Things,” in *Angewandte Chemie International Edition*, 6(11), 951–952., 2017, pp. 10–27.
- [8] I. K. N. Paramartha, T. Hamzah, B. Utomo, S. Luthfiyah, and E. ÖZDEMİRÇİ, “Lost Data and Transmition Speed Analysis on Incubator Analyzer Based IoT Technology,” *Int. J. Adv. Heal. Sci. Technol.*, vol. 2, no. 1, pp. 39–46, 2022, doi: 10.35882/ijahst.v2i1.7.

- [9] J. Prinyakupt and K. Roongprasert, *Verification Device for Temperature and Relative Humidity Inside the Infant Incubator via IoT*. 2019.
- [10] P. Kshirsgar, V. More, V. Hendre, P. Chippalkatti, and K. Paliwal, "IOT Based Baby Incubator for Clinic," *Lect. Notes Electr. Eng.*, vol. 570, no. January, pp. 349–355, 2020, doi: 10.1007/978-981-13-8715-9\_42.
- [11] N. Bin Kamarozaman and A. H. Awang, "IOT COVID-19 Portable Health Monitoring System using Raspberry Pi, Node-Red and ThingSpeak," pp. 107–112, 2021, doi: 10.1109/iswta52208.2021.9587444.
- [12] C. P. Oximeter and H. Sensor, "Pulse Oximeter and Heart-Rate Sensor IC for Wearable Health MAX30100 Pulse Oximeter and Heart-Rate Sensor IC for Wearable Health Absolute Maximum Ratings Supply Current in Shutdown," pp. 1–29, 2014, [Online]. Available: <https://pdf1.alldatasheet.com/datasheet-pdf/view/879178/MAXIM/MAX30100.html>.
- [13] H. Durani, M. Sheth, M. Vaghasia, and S. Kotech, "Smart Automated Home Application using IoT with Blynk App," *Proc. Int. Conf. Inven. Commun. Comput. Technol. ICICCT 2018*, pp. 393–397, 2018,

doi: 10.1109/ICICCT.2018.8473224.

- [14] V. Pravalika and C. Rajendra Prasad, "Internet of things based home monitoring and device control using Esp32," *Int. J. Recent Technol. Eng.*, vol. 8, no. 1 Special Issue 4, pp. 58–62, 2019.
- [15] F. Lopez, F. J. Torres, V. A. Ramirez, D. A. Nunez, R. Corona, and A. R. Lopez, "Raspberry pi for implementation of web technology in an automation process," *2019 IEEE Int. Autumn Meet. Power, Electron. Comput. ROPEC 2019*, no. Ropec, pp. 2–7, 2019, doi: 10.1109/ROPEC48299.2019.9057040.
- [16] F. Salih and S. A. Mysoon Omer, "Raspberry pi as a Video Server," *2018 Int. Conf. Comput. Control. Electr. Electron. Eng. ICCCEEE 2018*, pp. 1–4, 2018, doi: 10.1109/ICCCEEE.2018.8515817.
- [17] A. Ghosh, P. K. Kundu, and G. Sarkar, "Automated lux measurement for lighting design in indoor space using mobile sensor," *Proc. 2018 IEEE Appl. Signal Process. Conf. ASPCON 2018*, no. April 2021, pp. 106–109, 2018, doi: 10.1109/ASPCON.2018.8748775.
- [18] Y. Li, J. Cheng, and X. Wang, "An Optophone Based on Raspberry Pi and Android Wireless

- Communication,” *Proc. 2020 IEEE Int. Conf. Adv. Electr. Eng. Comput. Appl. AEECA 2020*, pp. 952–956, 2020, doi: 10.1109/AEECA49918.2020.9213587.
- [19] R. Riandi, O. B. Kharisma, and A. Ullah, “Pengembangan Sistem Deteksi Objek Menggunakan Sensor Ultrasonik HC-SR04 Berbasis IoT Terintegrasi Telegram Bot,” *Semin. Nas. Teknologi Inf.*, no. November, pp. 351–356, 2018.
- [20] A. R. Al Tahtawi, “Kalman Filter Algorithm Design for HC-SR04 Ultrasonic Sensor Data Acquisition System,” *IJITEE (International J. Inf. Technol. Electr. Eng.)*, vol. 2, no. 1, pp. 2–6, 2018, doi: 10.22146/ijitee.36646.
- [21] A. Yudhana, J. Rahmayanti, S. A. Akbar, S. Mukhopadhyay, and I. R. Karas, “Modification of manual raindrops type observatory ombrometer with ultrasonic sensor HC-SR04,” *Int. J. Adv. Comput. Sci. Appl.*, vol. 10, no. 12, pp. 277–281, 2019, doi: 10.14569/ijacsa.2019.0101238.
- [22] M. R. Hidayat, S. Sambasri, F. Fitriansyah, A. Charisma, and H. R. Iskandar, “Soft Water Tank Level Monitoring System Using Ultrasonic HC-SR04

- Sensor Based on ATmega 328 Microcontroller,” *Proceeding 2019 5th Int. Conf. Wirel. Telemat. ICWT 2019*, no. July, 2019, doi: 10.1109/ICWT47785.2019.8978229.
- [23] L. Meili and B. Yankang, “Embedded automatic control system for temperature, humidity and light intensity in agricultural greenhouses,” *ACM Int. Conf. Proceeding Ser.*, no. 866, 2018, doi: 10.1145/3284557.3284742.
- [24] B. Siregar, M. B. Hesananta, Seniman, and Fahmi, “Development of Gamelan music instruments using HC-SR04 sensor on arduino and operated using android-based applications,” *J. Phys. Conf. Ser.*, vol. 1882, no. 1, 2021, doi: 10.1088/1742-6596/1882/1/012140.
- [25] Elijah J. Morgan, “HC SR04 Ultrasonic Ranging Sensor Module,” *Eval. Tec. Sens.*, p. Nov. 16 2014, 2014, [Online]. Available: [https://www.pcbway.com/blog/News/New\\_product\\_in\\_gift\\_shop\\_\\_HC\\_SR04\\_Ultrasonic\\_Ranging\\_Sensor\\_Module.html](https://www.pcbway.com/blog/News/New_product_in_gift_shop__HC_SR04_Ultrasonic_Ranging_Sensor_Module.html).
- [26] F.- Puspasari, I.- Fahrurrozi, T. P. Satya, G.- Setyawan, M. R. Al Fauzan, and E. M. D. Admoko,

- “Sensor Ultrasonik HCSR04 Berbasis Arduino Due Untuk Sistem Monitoring Ketinggian,” *J. Fis. dan Apl.*, vol. 15, no. 2, p. 36, 2019, doi: 10.12962/j24604682.v15i2.4393.
- [27] Mutinda Mutava Gabriel, “Arduino Uno, Ultrasonic Sensor HC-SR04 Motion Detector with Display of Distance in the LCD,” *Int. J. Eng. Res.*, vol. V9, no. 05, pp. 936–942, 2020, doi: 10.17577/ijertv9is050677.
- [28] M. M. A. Weerasinghe, “3D Measurement Test Bench for Luminaires 3D Measurement Test Bench for Luminaires,” no. May, 2016.
- [29] P. S. Frima Yudha and R. A. Sani, “Implementasi Sensor Ultrasonik Hc-Sr04 Sebagai Sensor Parkir Mobil Berbasis Arduino,” *EINSTEIN e-JOURNAL*, vol. 5, no. 3, 2019, doi: 10.24114/einstein.v5i3.12002.
- [30] S. Kale and C. S. Khandelwal, “Design and implementation of real time embedded tele-health monitoring system,” *Proc. IEEE Int. Conf. Circuit, Power Comput. Technol. ICCPCT 2013*, vol. 4, no. 4, pp. 771–774, 2013, doi: 10.1109/ICCPCT.2013.6528842.